

SK-LLD05F

LED OPERATION LAMP





SK-LLD05F

FEATURES AND HIGHLIGHTS

The LED surgical shadowless lamp is composed of multiple lamp bulb. The bulb has a longer life than the traditional shadowless lamp. It can be round or petal-shaped. It is fixed on the balance arm suspension system. What's more, it is stable in positioning and can be moved vertically or cyclically to meet different heights during surgery.



Technical parameters

Diameter of lighthead (mm):	550
• Illumination at 1m (Lux):	150000
Brightness control range:	10-100% stepless adjustment
Color temperature (Kelvin):	4800±300
Color rendering index (CRI):	≥96
• Temperature rise (Surgeon head)(°C):	€2
• Temperature rise (Surgical field)(°C):	≤1
■ Total irradiance Ee (W/m2):	≤555
 Radiant power Ee/Ec (mW/m2lux): 	≪4
Effective focusing depth (cm):	60
Lighting spot size (cm):	10-24
 L1+L2 depth of illumination (cm): 	600
Bulb type:	LED

Bulb brand:	OSRAM
Bulb quantity:	65
Bulb power (w):	1
Average bulb life (hours):	≥50000

Technical configuration

✓ Rotating arm	1 set
✓ Balance arm	1 set
☑ C-arm	1 set
☑ Handle	1 pcs



Material technology

The lampshade shell and boom are selected from Baosteel's high-quality steel. The surface adopts the high-voltage electrostatic spraying process, and the imported environmentally friendly antibacterial plastic powder that used to ensures that the product meets the requirements of surgical hygiene. Also, this product has matte surface and no glint.




Bulb

It uses OSRAM high-quality LED light-emitting chips, the chip life is up to more than 50,000 hours, 40 times longer than the life of traditional halogen lamps.




Color temperature&illumination

It uses LED cold light source, the color temperature is 4800 \pm 300K, the illuminance can reach 150,000 Lux, which can realize stepless dimming and non-multi-level adjustment. While meeting high illuminance, according to the needs of different surgeons, it can adjust the lighting parameters, so that the surgeon's perception of light is soft and not dazzling.



Color rendering index


The color rendering index is as high as 96, which truly reflects the color of human tissues. It is suitable for various surgical scenes and greatly reduces the visual fatigue of medical staff due to long-term operations.





Temperature rise (surgical field)

Temperature rise (surgical field)(°C): ≤ 1 , this can avoid tissue drying due to high temperature and rapid blood clots at the wound, which will affect the operation.



Lamp holder structure

The lamp holder is equipped with multiple light sources and reflectors to focus on the working plane, which can effectively eliminate the shadows on the surgical site formed by the surgeon's head, shoulders and arms.



Operating handle

The detachable disinfection handle is made of high-strength ABS, which can be disinfected and sterilized at a high temperature above 135°, ensuring the durability and reliability of the handle.

















Research



Manufacturing



Maintenance





Saikang Medical Technology, Inc. 17800 Castleton St Ste 180, City of Industry, 91748, California. Tel.: +1 949648 2776

United Kingdom

 ${\tt UK\, Healthward\, International\, Ltd.}$ Dept. 111, 196 High Road Wood Green, N22 8HH, London. Tel.: +44 2032399738

Russia

Saikang Medical Russia LLC Truda 174, 454080 Chelyabinsk. Tel.: +7 (351) 214 5566 / 8811 / 1516

East Africa

Saikang Medical Solutions Ltd. Viraj Complex Unit 3, Mombasa Road, P.O. Box 14262-00800, Nairobi. Kenya. Tel.: +254 733 704 690

Middle East

Saikang Medical Supplies LLC X22-S03 England Cluster, International City, Dubai. United Arab Emirates Tel.: +20 128 8962497



Jiangsu Saikang Medical Equipment Co., Ltd. STOCK CODE: 870098

No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China

export@sksurgitech.com

www.sksurgitech.com















General catalogue